

**PT083 (axial) body dimensions:**

<b>Length</b>	8.43mm (.332")
<b>Diameter</b>	2.54mm (.100")
<b>Lead dimensions</b>	0.020" dia. X 1.500" long (min.)



**PT156 (axial) & SP156 (probe) body dimensions:**

<b>Length</b>	13.21mm (.520")
<b>Diameter</b>	4.75mm (.187")
<b>Lead dimensions</b>	0.028" dia. X 1.500" long (max.)

**PT083, PT156 & SP156 Electrical and Physical Specifications:**

Resistance value:	1KO (Std.) at 21.1°C. ±0.1%
Other resistance values:	from 0.10 to 5KO
Other tolerances:	±1% to ±0.05%
TCR characteristics:	+4300ppm/°C. (±50ppm/°C.), (between 25°C. and +100°C.)
Stability (no load):	to < ±0.02%/yr. @ 25°C.
Temperature:	-65°C. to +125°C.
<b>PT083</b> power rating:	0.05W Max
<b>PT156</b> power rating:	0.25W Max
<b>SP156</b> power rating:	0.25W Max

駿融企業有限公司 JIN ZON ENTERPRISE CO., LTD.  
104 台北市長安東路二段 171 號 4 樓之 3  
4F-3, No. 171, Sec. 2, Chang An E. Rd., Taipei, Taiwan, R. O. C.  
TEL: 886-2-27111093~5      FAX: 886-2-27310902  
E-mail: [jinzon@ms2.hinet.net](mailto:jinzon@ms2.hinet.net)      Http:// [www.jinzon.com.tw/](http://www.jinzon.com.tw/)