



JIN ZON ENTERPRISE CO., LTD.

4F-3, No. 171, Sec. 2, Chang An E. Rd.,
 Taipei, Taiwan, R. O. C.
 TEL: 886-2-27111093~5
 FAX: 886-2-27310902
 E-mail: jinzon@ms2.hinet.net
 Http:// www.jinzon.com.tw/

Hall sensor OHS01/5-24

RoHS compliant product

Sensors are operated by permanent magnets, sizes and parameters of which depend on user's applications.
 In case doubts please contact the producer



L – Length of wires depends on customer's requirement

all dimensions in mm

DATA SCAN		Unit	OHS01/5-24
Contact form			open drain (NPN)
Function			omnipolar switch
Operating voltage range	min	V _{DC}	4,5
	max		24
Max current consumption	max	mA	6
Output saturation voltage	max	mV	500
Output leakage current	max	μA	10
Output current	max	mA	25
Operating frequency	max	kHz	100
Operate point (B _{OP})	max	mT	6,0 (south or north)
Release point (B _{RP})	min	mT	0,5 (south or north)
Hysteresis (B _{hys} = B _{OP} - B _{RP})	typ	mT	1,8
Environment category acc. to IEC 68-2-1÷3			40/85/21
Housing			Plastic case

* - sensor is protected against reverse polarity connection

** - output current is limited internally (30-60mA)

Typical applications:

Automatic control systems, garage doors, elevators, washing machines, refrigerators.