


(Slide Potentiometer)


JSL5NH(2.5)-XXX

L:2.4J-SMD

- Character: Tiny size slide potentiometer for top adjustment type, travel=5mm (or 9mm)
- Element: Carbon Film; SMD type
- Function: For use in carry medical equipment, automotive electronic equipment, alarm system.
- Patented: approved by China

Character: Tiny size slide potentiometer for side adjustment type, travel=10mm





Patented: approved by China



(Slide Potentiometer)

JSL10N-Series



(Rotary Potentiometer)

JSP-RS16K1

• Character: Specially made for rotary potentiometer with push-pull switch and rotary switch.

Element: Bakelite or ceramic are available

Function: For use in any volume system which needs switch



(Rotary Potentiometer)

JRP24K1W

- Character: Twice potentiometer connection with shaft. It'll change both the potentiometer's value on same time when rotate the shaft. Closed type will avoid dusty.
- Element: Metal case
- Function: Use in all kinds of electronic equipment.

JIN ZON ENTERPRISE CO., LTD

http://www.jinzon.com.tw/

Address: 4F-3. No.171. Sec.2. Chang An E. Rd. Taipei. Taiwan. R.O.C.

Tel: 886-2-27111093~5

Fax: 886-2-27310902,27764624



- Character: Automatic replacement potentiometer for joystick or focus
- Element: Bakelite
- Function: For use in carry medical equipment, automotive electronic equipment, alarm system.

(Automatic Replacement type)

JRJ-16K1



(with switch)
JTS-RP16 Series

- Character: Rotary potentiometer with switch, and specially closed type to avoid dusty.
- Element: Plastics case
- Function: For use in carry medical equipment, automotive electronic equipment, alarm system, or digital controller



(Can rotate 360°) JRG24K/360°

- Character: Can rotate 360°,no pin pith design.
- Element: Glass fiber
- Function: Use in automatic rise-drop system



- Character: Heat-resistant (250PPM/°C) ; special made the distance of pin is 3mm x 3.5mm
- Element: (Ceramic film)
- Function: For use in carry medical equipment, automotive electronic equipment, alarm system.

Tel: 886-2-27111093~5