



Click on picture for other sizes

With PRC Custom Sensors you can select any value from 50O to 5KO
with exact TCRs from +3000ppm/°C to +4000ppm/°C in two "probe type" sizes:
Example of PRC's custom marking: 50O = PRC50, 1KO = PRC1K, 5KO = PRC5K, etc.

PRC(your value*)A (rect. axial) body dimensions:

- A) Height: 3.18mm (.125")
- B) Length: 9.14mm (.360")
- C) Width: 3.18mm (.125")

Lead dimensions: 0.020" dia. x 1" long (min.)

PRC(your value*)T (2-tab SMD) body dimensions:

- A) Height: 3.18mm (.125")
- B) Length: 9.14mm (.360")
- C) Width: 3.18mm (.125")

Tab dimensions: a=.075"; b=.075"; c=.100"; d=.260"

PRC(your value*)A & PRC(your value*)T Electrical and Physical Specifications:

Resistance value:	50O to 5KO @ 0°C
Tolerance:	to ±0.03%
TCR characteristics:	+3000ppm/°C. to +4000ppm/°C. (between 0°C. and +100°C.)
Stability (no load):	to <±0.005%/yr. at 25°C
Temperature:	65°C. to +150°C.
PRC(your value*)A Max Watts: 0.1W	
PRC(your value*)T Max Watts: 0.1W	

駿融企業有限公司 JIN ZON ENTERPRISE CO., LTD.
104 台北市長安東路二段 171 號 4 樓之 3
4F-3, No. 171, Sec. 2, Chang An E. Rd., Taipei, Taiwan, R. O. C.
TEL: 886-2-27111093~5 FAX: 886-2-27310902
E-mail: jinzon@ms2.hinet.net Http:// www.jinzon.com.tw/